


## Loox LED 2015

### LED Ribbon Light



- Ideal for direct lighting of furniture
- Can be cut-to-size
- High intensity light output


Length: 5000 mm (196 7/8")  
 Width: 10 mm (3/8")  
 Height: 2.5 mm (1/4")  
 Wattage: 40 (max. 3.8 m per driver)  
 Number of LEDs: 150 (30 per m)  
 Cable Length: 2.0 m (78 3/4")



Material: LED board; Colour: white

Light Colour	Lumen	Lumen per Watt	CRI	Item No.
6400 cool white	2808	78	78	833.73.410
3200 warm white	2412	67	67	833.73.400

Packing: 1 roll (includes 2 m mains lead)



**Daisy Chain Connector Cable, 500 mm (19 5/8")**

- With clip

Item No.
833.74.719


Packing: 1 pc.



**Splice Connector**

Item No.
833.74.720

Packing: 1 pc.




**Driver Connection Cable, 2 m (78 3/4")**

- With 12 V plug system and clip

Item No.
833.74.718

Packing: 1 pc.



Driver	page 22
Aluminum profile	page 19,20

## Loox LED 2015

### Aluminum Profile

- Surface mounted
  - With frosted cover
- Length: 2500 mm (98 3/8")  
 Width: 17 mm (11/16")  
 Height: 13 mm (1/2")  
 Material: aluminum; Colour: silver coloured anodized

Item No.
833.74.729

Packing: 1 pc.




#### End Cap

Material: plastic; Colour: silver coloured anodized

Item No.
833.74.730

Packing: 2 pcs.



- For recessed installation
  - With frosted cover
- Length: 2500 mm (98 3/8")  
 Width: 17 mm (11/16")  
 Height: 8 mm (5/16")  
 Material: aluminum; Colour: silver coloured anodized

Item No.
833.72.705

Packing: 1 pc.




#### End Cap

Material: plastic; Colour: silver coloured anodized

Item No.
833.72.709

Packing: 2 pcs.



- For angled installation
  - With frosted cover
- Length: 2500 mm (98 3/8")  
 Width: 18 mm (11/16")  
 Height: 13 mm (1/2")  
 Material: aluminum; Colour: silver coloured anodized

Item No.
833.72.715

Packing: 1 pc.




#### End Cap

Material: plastic; Colour: silver coloured anodized

Item No.
833.72.719

Packing: 2 pcs.




#### Note

The profiles depicted are only suitable for the LED 2015 strip lights. Insulating strip is provided for all profiles.

Loox 2011, HCN 03/2011: Dimensional data not binding. We reserve the right to alter specifications without notice.

Loox LED Driver  
Constant voltage 12 V Driver


FIXTURE B DRIVER



12 V  
System

- Suitable for all of the world's power systems
- With an integrated port for a wide selection of switches

Input voltage:	100-240 V; 50-60 Hz
Output voltage:	DC 12 V
Degree of protection:	IP 20
Number of slots:	6 for lights 1 for switch 1 for mains lead



Length	Width	Height	Wattage	Item No.
155 mm (6 1/8")	45 mm (1 3/4")	20 mm (13/16")	0.5 – 15	833.74.900
165 mm (6 1/2")	50 mm (2")	28 mm (1 1/8")	2.4 – 30	833.74.901

Packing: 1 pc. (does not include mains leads, see below for ordering information)

TO BE VERIFIED

Mains leads	page 24
Switches	page 23
Extension leads	page 24

Loox 2011, HCN 03/2011: Dimensional data not binding. We reserve the right to alter specifications without notice.