



BARRIER FREE

PL1

CADET RIGHT HEIGHT™ ELONGATED PRESSURE-ASSISTED 6L TOILET

VITREOUS CHINA

CADET RIGHT HEIGHT™ ELONGATED PRESSURE-ASSISTED 6L TOILET



2467 016

- Vitreous china
- Low-consumption (6.0 Lpf/1.3 gpf)
- EverClean® surface inhibits the growth of stain- and odor-causing bacteria, mold, and mildew on the surface
- Elongated 16-1/2" (419mm) high bowl rim for accessible applications
- Pressure-assisted siphon jet flush action
- Fully-glazed 2-1/8" (54mm) trapway) ball pass
- Generous 10 x 12" (254x305mm) water surface area
- Close-coupled Flushometer tank*
- Metal chrome trip lever
- Speed Connect™ tank/bowl coupling system
- Sanitary dam on bowl
- 2 bolt caps
- 100% factory flush tested
- 12" (305mm) Rough-in

Separate Component Parts:

- ☐ **3483 001** Elongated 16-1/2" (419mm) high Universal Bowl with 2 bolt caps
- ☐ **4142 016** Flushometer tank complete with coupling components

Nominal Dimensions:

768 x 521 x 781mm
(30-1/4" x 20-1/2" x 30-3/4")

Fixture only, seat and supply by others

Recommended static pressure range
25 psi - 80 psi

Alternate Configurations Available:

- ☐ **4142 600** Tank with tank cover locking device
- ☐ **4142 800** Tank with right hand trip lever
- ☐ **4142 900** Tank complete with right hand trip lever and tank cover locking device


Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2-2008 / CSA B45.1-08 for Vitreous China Fixtures

To Be Specified

- ☐ Colour: ☒ White ☐ Bone ☐ Linen ☐ Black
- ☐ Seat: American Standard #5324 019 "Rise and Shine" (with easy to clean lift-off hinge system) solid plastic closed, elongated front seat with cover. See price page.
- ☐ Seat: #5321 110 EverClean® Elongated Seat with Slow Close Snap-Off Hinges
- ☒ Alternate Seat:
- ☐ Supply with stop:



NOTES:

THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305mm (12") FROM FINISHED WALL TO C/L OF OUTLET.

SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.

FOR ADDITIONAL INFORMATION REFER TO INSTALLATION INSTRUCTIONS SUPPLIED. IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2


These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.



When installed so top of seat is 432 to 483mm (17" to 19") from the finished floor.

MEETS THE AMERICAN DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USEABLE BUILDING FACILITIES-CHECK LOCAL CODES.

* Flushometer tank system by Flushmate® Div. of Sloan Valve Co.



PLUMBER TO VERIFY SEAT SPECIFICATION

Model #	5901	5905	5910
A	18-9/16" (471mm)	18-9/16" (471mm)	18-3/16" (462mm)
B	14-3/8" (365mm)	14-3/16" (360mm)	14-3/16" (360mm)
C	7-7/8" (200mm)	7-5/8" (194mm)	7-7/8" (200mm)
D	3-1/2" (89mm)	3" (76mm)	3-1/2" (89mm)
E	5-1/2" (140mm)	5-1/2" (140mm)	5-1/2" (140mm)
Ring Thickness	7/8" (22mm)	1" (25mm)	1" (25mm)
Ring Thickness with Bumper	1" (25mm)	1-1/8" (29mm)	1-1/8" (29mm)

COMMERCIAL TOILET SEATS

- Open front toilet seat less cover
- Injection molded solid polypropylene
- Fits elongated bowl
- Features large molded-in bumpers
- External check hinge with 304 Series stainless steel hinge posts stops seat 11° beyond vertical
- Optional EverClean™ antimicrobial surface inhibits the growth of stain and odor causing bacteria, mold, and mildew

☐ **5901 100** Elongated Heavy Duty, open front seat less cover

☒ **5901 110** Same as 5901 100 with EverClean™ Surface

☐ **5905 100** Elongated Extra Heavy Duty, open front seat less cover

☐ **5905 110** Same as 5905 100 with EverClean™ Surface


☐ **5910 100** Elongated Extra Heavy Duty Plus, open front seat less cover

☐ **5910 110** Same as 5910 100 with EverClean™ Surface

SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified

☐ Colour: White



5901 100



5905 100



5910 100