

TOTO®

CST744SL

Drake® Close Coupled Toilet, ADA, 1.6GPF

FEATURES

- G-Max® flushing system, low consumption (1.6GPF/6.0LPF)
- Universal Height
- Two-piece design with high-profile tank
- Elongated front bowl and tank set, less seat
- Chrome trip lever
- 12" Rough-in, less supply
- ADA compliant

MODELS

- CST744SL
Elongated bowl, 12" rough-in, less seat
- CST744SLB*
Same as above with bolt down lid (special order)
- CST744SLD*
Same as CST744SL with insulated tank (special order)
- CST744SLDB*
Same as CST744SL with bolt down lid & insulated tank (special order)
- CST744SLR*
Same as CST744SL with right hand trip lever (special order)

COMPONENTS

- C744EL - Elongated Front Bowl
- ST743S - Tank and Cover only - Left-hand trip lever
- ST743SR - Tank and Cover only - Right-hand trip lever
- SS114 SoftClose® seat (sold separately)
- SS204 SoftClose® seat (sold separately)
- SC534 Seat (sold separately)
- SC134 Seat (sold separately)

COLORS/FINISHES

- Standard
 - #01 Cotton
 - #03 Bone
 - #11 Colonial White
 - #12 Sedona Beige
 - #51 Ebony

PRODUCT SPECIFICATION

The two-piece G-Max flushing system toilet shall be 1.6GPF/6.0LPF. Toilet shall be universal height and ADA compliant. Toilet shall have high-profile tank, elongated front bowl and chrome trip lever. Toilet shall be TOTO Model CST744SL_____.



G-MAX
FLUSHING SYSTEM BY TOTO®

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1,
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- ADA compliant (when installed with trip lever located on the approach side)



CST744SL

Drake® Close Coupled Toilet, ADA, 1.6GPF/6.0 GPF




SPECIFICATIONS

- Water Use 1.6 GPF/6.0LPF
- Flush System G-Max
- Min. Water Pressure 8 psi (static)
- Water Surface 10-3/8" x 8-1/4"
- Trap Diameter 2-1/8"
- Rough-in 12"
- Trap Seal 2-3/8"
- Warranty One Year Limited Warranty
- Material Vitreous china
- Shipping Weight C744EL - 56.5lbs
ST743S - 35lbs
- Shipping Dimensions C744EL
29-1/2"L x 16"W1
x 10-1/4"W2 x 18-1/4"H

ST743S
20-1/8"L x 8-1/4"W
x 15-1/2"H

INSTALLATION NOTES

Back-to-Back Toilet Installations:
TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



TOTO.

These dimensions and specifications are subject to change without notice

Features

- Siphon jet.
- 3/4" top spud.
- Includes inlet and outlet spuds and hangers.
- 1.0 gpf (3.8 lpf).

Material

- Vitreous china.

Components

Additional included component/s: Urinal, Inlet Spud, Outlet Spud, and Hangers.



ADA

Codes/Standards

ASME A112.19.2/CSA B45.1
DOE - Energy Policy Act 1992
ADA
ICC/ANSI A117.1




KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	7	Black Black™



Spud Detail

Technical Information

All product dimensions are nominal.

Flush outlet technology: Siphon jet

Spud size: inlet, Top

Max. Water per Flush: 1 gal (3.8 L)

Notes

Install this product according to the installation guide.

Refer to manufacturer's instructions and local codes for flush valve requirements.

ADA compliant when installed to the specific requirements of these regulations.

Features

- Powered by the 30-year Hybrid Energy System.
- Intended for urinal installations with 3/4-inch top spud coupling connection.
- 1 gallon per flush (gpf) for low water consumption.
- Piston technology offers reliable and accurate performance across pressures.
- Activation distance is factory set - no adjustments on-site.
- Chloramine resistance on all rubber exposed to waterway.
- Manual courtesy flush button.
- 24-hour sentinel flush operates automatically if unit not flushed for 24 hours.



ADA

CSA B651

OBC

Codes/Standards

ASME A112.18.1/CSA B125.1

CSA B64

CSA B125.3

ASSE 1037

ADA

ICC/ANSI A117.1

CSA B651

OBC

KOHLER® Electronic Faucets, Valves, and Controls - Five-Year Limited Warranty

See website for detailed warranty information.


Available Color/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------

	CP	Polished Chrome
--	----	-----------------

*10-3/4" (273 mm) minimum with a
6" (152 mm) critical level above the fixture



Technical Information

All product dimensions are nominal.

Power source: 9V, included

Notes



Install this product according to the installation guide.

Pressure over 80 psi (552 kPa) is not recommended on most plumbing fixtures.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Washbasin # 030050..00 / 030050..30

| < 500 mm > |



Washbasin	Dimension	Weight	Order number
with overflow, with tap platform, 500 mm			
Colors			
00 White Alpin			
Variant			
p	500 x 360 mm	14,100 kg	030050..00
p p p	500 x 360 mm	14,100 kg	030050..30

Sanitary ceramics with the special WonderGliss surface finish will remain clean and attractive-looking for a long time to come.
When ordering WonderGliss please add a "1" as eleventh digit to the model number.

Accessory	Dimension	Weight	Order number
Siphon cover for # 030050, 075045, 030160, 030155	165 x 240 mm	5,800 kg	086517

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished ceramic piece.



EUROPLUS Lavatory Centerset S-Size

MODEL # 33170

GROHE CANADA, INC. | 5900 Avebury Road, Mississauga, Ontario, Canada L5R 3M3
Phone: 905-271-2929 | Fax: 905-271-9494 | info@grohe.ca

Pure Freude
an Wasser

GROHE



Product Description: Lavatory Centerset S-Size

Standard Specification:



- Single hole installation
- Metal lever
- GROHE SilkMove® ceramic cartridge
- GROHE StarLight® finish
- Adjustable flow rate limiter
- Adjustable minimum flow rate approx. 1.0 gpm
- SpeedClean flow control
- Pop-up waste set
- Stainless Steel Braided Flexible Supplies
- Temperature limiter
- GROHE QuickFix™ Plus installation system with centering support

Applicable Codes & Standards:

- Energy Policy Act of 1992
- NSF 61
- ASME A112.18.1/CSA B125.1
- US Federal and State material regulations
- EPA WaterSense®
- ICC/ANSI A117.1

Color:

- 33170 002 GROHE StarLight®
Chrome
- 33170 EN2 Brushed Nickel inf



QSL1515/6 SPECIFICATION

Model QSL1515/6 is a single bowl, ledgeback sink manufactured by Franke Kindred Canada Limited from 20 gauge, 18-8 stainless steel. Product has a bright mirror finished rim and satin finished bowl. Sink is fully undercoated. Basket strainer waste fitting (3 1/2", 89 mm) and installation kit are included. Sink is backed with a limited buyer lifetime warranty.

- O.D. 15 7/16" x 15 1/8" x 6" (39 x 38 x 15 cm)
- Recommended for minimum 18" cabinet

QSL1515/6/2 2 hole - 1 1/2" diameter, 4" center-to-center [11.8 x 10.9 x 15.2]

QSL1515/6/1 1 hole on center [11.8 x 10.9 x 15.2]



see what Delta can do™

Classic Single Handle Bar/Prep Faucet

Model Number: 1903-DST



Features & Benefits

- DIAMOND Seal Technology features a valve embedded with diamonds to ensure like-new operation for the life of the faucet
- Meets standards set by Americans with Disabilities Act
- 2-hole 4 in. installation
- High-arc spout swivels 180°
- 1.50 gpm @ 60 psi, 5.7 L/min @ 414 kPa
- Assembled dimensions: 10 in. H x 5 in. D x 5 in. W

Smart Features

- ♿ ADA Compliant
- ◆ DIAMOND™ Seal Technology
- 💧 Water-Efficient
- ✓ Legislation Compliant

Product Specifications

NUMBER OF HANDLES:	1
TALL/HIGH-ARC:	No
PULL-OUT/PULL-DOWN:	No
WITH SIDE SPRAYER:	No
WITH SOAP/LOTION DISPENSER:	No
VALVE TYPE:	DIAMOND(TM) Seal Valve
FLOW RATE:	1.50 gpm @ 60 psi, 5.7 L/min @ 414 kPa
HOSE LENGTH:	
HOLES/WIDTH:	2-hole 4 installation
SPOUT LENGTH:	5-13/16
SPOUT TOTAL HEIGHT:	10
SPOUT HEIGHT DECK TO AERATOR:	5-31/32